

Unit Heaters

Built for quality and performance, our unit heaters offer better performance, heavier gauge construction, and increased installation flexibility, all in a nicer looking package. Equipped with variable speed motors (excluding UH-18) the unit heaters give you the ability to fine tune the balances between performance and efficiency.

These heaters are another excellent way to convert your hot water to forced air heat. Our unit heaters also work excellent in combination with hot water in-floor heat. This combination gives you the comfort of in-floor heat as well as the quick recovery of forced air all from the same heating system.

All our unit heaters can be easily converted from a right hand water supply to a left hand water supply. Each unit heater is designed to be used with a 110 volt thermostat. Thermostat and speed control sold separately.



UH-18



UH-95



UH-140



UH-190

Unit Heater Specifications Internal Specifications using water. Entering Air Temperature = 60°

MODEL	BTUs EWT-200°	BTUS EWT-180°	CFM - Amps	GPM	APD	Speeds	Approx FOH-WPD	Approx LWT at 200°	Aprox LWT at 180°	HP
UH-18	19,732	16,881	180 - 1.4	7	.05	NO	2.16	194°	175°	1/30
UH-60	64,923	55,506	700 - 1.4	11	.11	YES	2.73	187°	169°	1/30
UH-95	102,058	87,243	935 - 1.6	12	.10	YES	2.47	182°	165°	1/20
UH-140	158,184	135,066	1,770 - 3.9	12	.20	YES	2.23	172°	156°	1/4
UH-190	206,831	176,585	2,278 - 4.9	14	.25	YES	2.66	169°	154°	1/4
UH-225	244,239	208,638	2,690 - 4.1	16	.19	YES	2.87	168°	153°	1/4